

Dimensiones (mm) - Motor a Prueba de Explosión

CARCASA	A	AA	AB	AC	AD	B	BA	BB	C	DIMENSIONES DEL EJE					
										D	E	ES	F	G	GD
90S	140	38	164	179	214	100	42	131	56	24/6	50	36		20	
90L						125		156					8		7
100L	160	44	188	199	224		50	173	63	28/6	60	45		24	
112M	190	48	220	223	243	140		183	70						
132S	216	51	248	270	271		55	188	89	38/6	80	63	10	33	
132M						178		226							8
160M	254	64	308	312	322	210	65	254	108	42/6			12	37	
160L						254		298							
180M	279	80	350	358	342	241	75	294	121	48/6	110	80	14	42,5	9
180L						279		332							
200M	318	82	385	399	370	267	85	332	133	55/6			16	49	10
200L						305		370							
225S/M	366	80	436			285	105	391	149	55/6 *		100			
				472	413	311				60/6				53	
250S/M	406		506			349	138	445	168	60/6 *			18		11
		100				368				65/6	140	125		58	
280S/M	457		557		551	419	142	510	190	65/6 *			20	67,5	12
				610		406				65/6 *			18	58	11
315S/M	508	120	628		573	457	152	558	216	75/6 *	170	160	22	71	14
						560				75/6 *	140	125	20	67,5	12
355S/M	610	140	750	780	672	630	200	760	254	100/6	210	200	18	90	16

Nota: (*) Dimensiones de la punta de eje para Motores 11 polos

CARCASA	H	HA	HC	HD	HD'	K	L	S1	D1	RODAMIENTOS	
										D.E.	N.D.E.
90S	90	12	177		304	10	318		DM8	6205-ZZ	6204-ZZ
90L							341	M25x 1.5			
100L	100	15	200		324		384		DM10	6206-ZZ	6205-ZZ
112M	112	17	237	222	355	12	394			6307-ZZ	6206-ZZ
132S	132	19,5	282	330	403		451	M32x 1.5	DM12	6308-ZZ	6207-ZZ
132M							489				
160M	160	22	315	370	482		598				
160L						14,5	652	2x M40x 1.5	DM16	6309-C3	6209-Z-C3
180M	180	28	367	422	522		664			6311-C3	6211-Z-C3
180L							702				
200M	200	30	403	477	570		729			6312-C3	6212-Z-C3
200L						18,5	767	2x M50x 1.5			
225S/M	225	34	475	550	638		817				
							847			6314-C3	
250S/M	250		500	575	663	24	923		M20		
280S/M	280	42	600	693	831		1036			6316-C3	
							1126	2x M63x 1.5		6314-C3	
315S/M	315	52	640	728	888	28	1156			6319-C3	6316-C3
							1399			6316-C3	6314-C3
355S/M	355	50	755	864	1027		1469		M24	NU-322-C3	6319-C3

