

Características Técnicas Contactores

Contactores		CWB 9	CWB 12	CWB 18	CWB 25	CWB 32	CWB 38	CWB 50	CWB 65	CWB 80
Régimen AC-3	Corriente le max. (A)	9	12	18	25	32	38	50	65	80
	Potencia 380V (HP)	5,5	7,5	10	15	20	25	30	40	50
	Man. / hora a plena carga	1200	1200	1200	1200	1200	1200	1200	1200	1200
Régimen AC-1	Carga resistiva le = lth (A)	25	25	32	40	50	50	90	110	110
N° de Polos		3 polos	3 polos	3 polos	3 polos	3 polos	3 polos	3 polos	3 polos	3 polos
Fusible máximo (A)		25	25	35	50	50	50	100	125	125
Cons. Bobina CA 50Hz - "Pegar"/"Mantener" (VA)		90/9	90/9	90/9	90/9	90/9	90/9	202/27	202/27	202/27
Peso CA/CC (Kg)		0,37/0,49	0,37/0,49	0,37/0,49	0,40/0,53	0,40/0,53	0,40/0,53	0,91/1,03	0,91/1,03	0,91/1,03
Dimensiones	Ancho (mm)	45	45	45	45	45	45	54	54	54
	Altura (mm)	78,4	78,4	78,4	85	85	85	115	115	115
	Profundidad CA/CC (mm)	89,5/98,5	89,5/98,5	89,5/98,5	93/102,2	93/102,2	93/102,2	120,6	120,6	120,6
Relés de sobrecarga		RW 27-2D						RW 67-5D		

Contactores		CWB 95	CWB 110	CWB 125	CWB 150	CWB 180	CWB 225	CWB 265	CWB 340	CWB 400	CWB 500
Régimen AC-3	Corriente le max. (A)	95	110	125	150	180	225	265	340	400	500
	Potencia 380V (HP)	60	75	75	100	125	150	175	220	250	300
	Man. / hora a plena carga	1200	1200	500	500	500	600	500	500	500	500
Régimen AC-1	Carga resistiva le = lth (A)	140	150	175	225	275	320	350	420	550	550
N° de Polos		3 polos	3 polos	3 polos	3 polos	3 polos	3 polos	3 polos	3 polos	3 polos	3 polos
Fusible máximo (A)		200	250	315	355	355	355	1000	1000	1000	1000
Cons. Bobina CA 50Hz - "Pegar"/"Mantener" (VA)		426/27	426/27	420/45	430/11	430/11	430/11	580/14,5	580/14,5	580/14,5	580/14,5
Peso CA/CC (Kg)		1,62	1,62	1,66	3,3	3,3	3,3	5,2	5,2	5,2	5,2
Dimensiones	Ancho (mm)	72	72	72	110	110	110	140	140	140	140
	Altura (mm)	148,6	148,6	148,6	194	194	194	213,8	213,8	213,8	213,8
	Profundidad CA/CC (mm)	144,5	144,5	144,5	185,6	185,6	185,6	216	216	216	216
Relés de sobrecarga		RW 117-3D3			RW317-5D3-U165	RW317-5D3-U230		RW317-5D3-U310	RW407-1D3-U600	RW407-1D3-U840	

Contactores para Condensador		CWBC 18	CWBC 25	CWBC 32	CWBC 50	CWBC 65
Potencia Reactiva para bancos de capacitores. Régimen AC-6B. Temperatura Ambiente = 55° C	220-230Vca	8 kVAr	11 kVAr	15 kVAr	25 kVAr	30 kVAr
	380-415Vca	15 kVAr	20 kVAr	26 kVAr	40 kVAr	50 kVAr
	440VCA	16 kVAr	23 kVAr	30 kVAr	45 kVAr	60 kVAr
N° de Polos		3 polos	3 polos	3 polos	3 polos	3 polos
Corriente le max (A)		22	31	40	60	77

Contactores CWB

Contactores Tripolares - Bobina CA - 50/60hz

Código	Referencia	Corriente AC-3 (A)	Bobina (Vca)	Contactos Auxiliares	
				NA	NC
12660800	CWB9-11-30 D02	9	24	1	1
12660801	CWB9-11-30 D13	9	110	1	1
12220434	CWB9-11-30 D23	9	220	1	1
12660802	CWB9-11-30 D33	9	380	1	1
12660803	CWB12-11-30 D02	12	24	1	1
12660804	CWB12-11-30 D13	12	110	1	1
12220435	CWB12-11-30 D23	12	220	1	1
12660805	CWB12-11-30 D33	12	380	1	1
12660806	CWB18-11-30 D02	18	24	1	1
12660807	CWB18-11-30 D13	18	110	1	1
12220436	CWB18-11-30 D23	18	220	1	1
12660848	CWB18-11-30 D33	18	380	1	1

